


Indoor Ribbon Cable (4-24F)



Temperature Range:

Storage & Operating:- 20°C to 60°C


Standards:

Comply with standard YD/T1258.2-2003 and IEC 60794-2-30/31

Technical Parameter:

Fiber Count	Cable Diameter (mm)	Weight (Kg/Km)	Tensile Strength (N)		Crush Resistance		Minimum Bending radius (mm)	
			Short-term	Long-term	Short-term	Long-term	Static	Dynamic
2	2.5 x 3.5	17.3	200	80	500	200	30	50
4	2.5 x 3.5	7.4	200	80	500	200	30	50
6	2.5 x 4.0	8.2	200	80	500	200	30	50
8	2.5 x 4.5	9.3	200	80	500	200	30	50
12	2.5 x 5.0	10	200	80	500	200	30	50
24	2.5 x 5.5	10.8	200	80	500	200	30	50

Indoor Distribution Cable (2-48F)



Temperature Range:

Storage & Operating:- 20°C to 60°C

Standards:

Comply with standard YD/T1258.2-2003 and IEC 60794-2-30/31

Technical Parameter:

Fiber Count	Cable Diameter (mm)	Weight (Kg/Km)	Tensile Strength (N)		Crush Resistance		Minimum Bending radius (mm)	
			Short-term	Long-term	Short-term	Long-term	Static	Dynamic
2	5	20	15	600	200	1000	200	20
4	5.10	20	22	600	200	1000	200	20
6	5.30	22	23	600	200	1000	200	20
8	6	25	27	600	200	1000	200	20
12	6.6	28	35	600	200	1000	200	20
24	7.2	31	40	600	200	1000	200	20
48	7.9	36	45	600	200	1000	200	20