


### Indoor Breakout (Cable 2-48F)



**Temperature Range:**

Storage & Operating:- 20°C to 60°C


**Standards:**

Comply with standard YD/T1258.2-2003 and IEC 60794-2-30/31

### Technical Parameter:

Fiber Count	Cable Diameter (mm)	Weight (Kg/Km)	Tensile Strength (N)		Crush Resistance		Minimum Bending radius (mm)	
			Short-term	Long-term	Short-term	Long-term	Static	Dynamic
2	7	45	1500	500	1000	300	20	10
4	7	47	1500	500	1000	300	20	10
6	8.3	64	1500	500	1000	300	20	10
8	9.5	88	1500	500	1000	300	20	10
12	11.5	105	1500	500	1000	300	20	10
24	13.5	142	1500	500	1000	300	20	10
48	17.5	175	1500	500	1000	300	20	10

### Indoor Drop Cable (1-2F)



**Temperature Range:**

Storage & Operating:- 20°C to 60°C

**Standards:**

Comply with standard ITU.T G.652D / G.657A

### Technical Parameter:

Fiber Count	Cable Diameter (mm)	Weight (Kg/Km)	Tensile Strength (N)		Crush Resistance		Minimum Bending radius (mm)	
			Short-term	Long-term	Short-term	Long-term	Static	Dynamic
1-2	2.0 X 3.0 +/- 0.2mm	8	80	40	1000	500	30	25