



Standard

- Electrical performance guaranteed to meet or exceed ANSI/TIA-568B Category 5e and ISO/EIC specifications.
- Independently tested and verified intertek(ETL).
- Ideal for Data center architectural requirements.
- Stranded cable for maximum flexibility.
- Available with different plug mold.
- Available with different color of cable.
- Available with different length.

Conductor

Conductor	stranded bare copper 24AWG
Insulation	HDPE
Total number of insulated conductors	8, twisted in 4 pairs
Color code	White-Blue/Blue, White-Orange/Orange White-Green/Green, White-Brown/Brown
Individual pair shield	None
Overall shield	None
Drain wire	None

Nominal Transmission Characteristics

Res.	Length	Prop. Delay	Delay Skew	Freq.	Insertion Loss	NEXT	RL	ACR-N	ACR-F	PS NEXT	PS ACR-N	PS ACR-F
Ω	Max.	ns	ns	MHz	dB	dB	dB	dB	dB	dB	dB	dB
i	100m	555	50	1	3	60.0	17.0	57.0	57.4	57.0	54.0	54.4
				4	4.5	53.5	17.0	49.1	45.4	50.5	46.1	42.4
				8	6.3	48.6	17.0	42.3	39.3	45.6	39.3	36.3
				10	7.1	47.0	17.0	39.9	37.4	44.0	36.9	34.4
				16	9.1	43.6	17.0	34.5	33.3	40.6	31.5	30.3
				20	10.2	42.0	17.0	31.8	31.4	39.0	28.8	28.4
				25	11.4	40.3	16.0	28.9	29.4	37.3	25.9	26.4
				31.25	12.9	38.7	15.1	25.9	27.5	35.7	22.9	24.5
				62.5	18.6	33.6	12.1	15.0	21.2	30.6	12.0	18.5
				100	24	30.1	10.0	6.1	17.4	27.1	3.1	14.4

Part No. Legend					
Patch Cord	Category	Shield	Jacket	Length	Color Code
PC	5E	UTP	1 - PVC 2 - PE 3 - LSZH	1 MTR - 01 2 MTR - 02 Increase by every one meter	GREY (GY) BLUE (BU) RED (RD) YELLOW (YL) WHITE (WH) GREEN (GR) ORANGE (OR) BLACK (BL) PURPLE (PL)
Part No.	Item Description				
PC5EU101GY	PATCH CORD CAT 5E UTP 1 METER GREY				
PC5EU301GY	PATCH CORD CAT 5E UTP LSZH 1 METER GREY				