

Cat.6 patch panel.

Parameter

- Meet ISO/IEC 11801,TIA/EIA568C.
- British type.
- Connector & cable management
- Fit for wires AWG22-26.
- Plug insertion life 750 cycles Min.
- Dielectric strength:When applied AC 750V or DC 1000V 1 minute between adjacent terminal NO change.
- Material:Using PC/ABS for cover,PC for module, phosphor bronze for IDC wire post.
- Krone IDC.



Part No.	Item Description
PP06U24L PP06U48L	19" CAT 6 UNSHIELDED PATCH PANEL 24 PORT RJ45 LOADED 19" CAT 6 UNSHIELDED PATCH PANEL 48 PORT RJ45 LOADED

CAT 5E patch panel.

Parameter

- Parameter: professional industrial design, plastic cover with metal channel.
- Port Numbers: color printed.
- Meet ISO/IEC 11801,TIA/EIA568C.
- Every keystone can be disassembled alone (M255A-1,CAT.5e keystone jack).
- Connector & cable management
- Fit for wires AWG22-26.
- Plug insertion life 750 cycles Min.
- Dielectric strength: When applied AC 750V or DC 1000V 1 minute between adjacent terminal NO change.
- Material:Using PC/ABS for cover,PC for module, phosphor bronze for IDC wire post.
- 110 IDC.
- 19".1U,24 ports.



Part No.	Item Description
PP5EU24L PP5EU48L	19" CAT 5e UNSHIELDED PATCH PANEL 24 PORT RJ45 LOADED 19" CAT 5e UNSHIELDED PATCH PANEL 48 PORT RJ45 LOADED